WAC LIGHTING

Recessed Trimless Channel

Responsible Lighting®

项目名称:		灯位号:	
产品图片	线图		
	OS2CL04-FE-BK	200	98.7
产品描述	OS2CL01-BK	304.8 1219.2 2438.4 3667.6	72.5

STRUT 轨道适配于 WAC STRUT 低压轨道系统灯具,多种安装方式,适配多种天花安装。DC48V 输入,最大总负载电流可达 12.5A。可以任意形状拼接,满足不同的照明应用环境需求,广泛应用于办公,商业等照明空间场所。

产品特性

• 主体材质: 铝合金灯体

• 表面处理: 静电粉末喷涂/阳极氧化

安规认证: /

• 防护等级: IP20

• **绝缘等级**: Class I

产品规格

• 长度: 0.3M/1.2M/2.4M/3.6M

• 输入电压: DC48V

• **调光控制**: ON-OFF/0-10V/ELV/DMX512/无线及手机 APP 控

制

• **产品重量**: 约

0.8Kg(0.3M),2.24Kg(1.2M),4.56Kg(2.4M),6.8K

g(3.6M),不含包装

订购模型

Model	Length		Finish
OS2CL04-FE	04 1.2M Trimless Recessed Feed End	Required Power Feed Run	
OS2CL08-FE	08 2.4M Trimless Recessed Feed End	Connected Power Unit Required	BK Black
OS2CL12-FE	12 3.6M Trimless Recessed Feed End	See page 44 (sold separately)	

示例: OS2CL04-FE-BK

Model	Length		Finish
OS2CL01 OS2CL04 OS2CL08 OS2CL12	01 0.3M Trimless Recessed Channel04 1.2M Trimless Recessed Channel08 2.4M Trimless Recessed Channel12 3.6M Trimless Recessed Channel	To extend channel runs after feed end	BK Black

示例: OS2CL01-BK

无边嵌装连接器配件

WAC Lighting www.waclighting.com (US) www.waclighting.com.cn (China) Headquarters

44 Harbor Park Drive • Port Washington, NY Phone (516) 515.5000 • Fax (516) 515.5050 WAC Lighting(Shanghai)

14,Lane 299, Bi Sheng Road,Shanghai 201204 Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

WAC Lighting 保留对产品进行不定期设计更新的权利。2022-09-08

WAC LIGHTING

Responsible Lighting®

Recessed	Trimless	Channel

Model	Description	Pic
OS2CL-FEB	Feed End Junction Box 5in junction box with side knockouts. Includes BK and WT covers	
OS2CSR-I-BK	I Connector Joins two channel sections with electrical continuity	
OS2C-ID-BK	Dead I Connector Joins two channel sections without electrical continuity	
OS2CL-L-BK OS2CL-L-WT	L Connector Joins two channel sections 90°	
OS2CL-T-BK OS2CL-T-WT	T Connector Joins three channel sections	
OS2CL-X-BK OS2CL-X-WT	X Connector Joins four channel sections	
OS2CL-IC-BK OS2CL-IC-WT	Inside Corner Joins ceiling to wall channel sections	

WAC LIGHTING

Responsible Lighting®

Recessed	Trim	اعددا	Chann	Δ
Recessed	- i rimi	iess (cnann	e

目名称:	灯位号:	
------	------	--

OS2CL-OC-BK OS2CL-OC-WT	Outside Corner Joins wall to wall channel sections	
OS2CPSL-IC-BKBK OS2CPSL-IC-WTBK	Surface/Suspended to Recessed Corner Joins suspended or surface mounted channel to recessed trimless channel	
OS2CL-EC-BK	End Cap Additional end cap	

无边嵌装配件

Model	Description	Pic
OS2CR-CLIP-BK	Mount Clip Support recessed channel with 1/4 - 20 threaded rod (rod by others)	
OS2C-C96-BK	Cable Suspension Support recessed channel from plenum ceiling. Includes 96in aircraft cable; may be field cut	
OS2C-S96-BK	Stem Suspension Support recessed channel from plenum ceiling. Includes two 48in stem; may be field cut	
OS2C-LOOP-BK	Suspension Loop Mechanical loop Supports up to 15 lb	6

WAC LIGHTING

Responsible Lighting®

Recessed	Trimless	Channel	ı

项目名称:		灯位号:	
OS2SN-1-BK	VACANCY/PHOTO SENSOR		
OS2C-COV08-BK	Channel Cover 2.4M 2.4M length may be field cut, Suitable for top or bottom channel coverage.		>