WAC LIGHTING

Suspended Channel

Responsible Lighting®


项目名称:	

灯位号:

产品图片



线图



产品描述

STRUT 轨道适配于 WAC STRUT 低压轨道系统灯具,多种安装方式,适配多种天花安装。DC48V 输入,最大总负载电流可达 12.5A。可以任意形状拼接,满足不同的照明应用环境需求,广泛应用于办公,商业等照明空间场所。

产品特性

• **主体材质**: 铝合金灯体

• 表面处理: 静电粉末喷涂/阳极氧化

安规认证: /

• **防护等级**: IP20

• 绝缘等级: Class I

产品规格

• 长度: 0.3M/1.2M/2.4M/3.6M

• 输入电压: DC48V

• **调光控制**: ON-OFF/0-10V/ELV/DMX512/无线及手机 APP 控

制

• **产品重量**: 约

0.8Kg(0.3M),2.24Kg(1.2M),4.56Kg(2.4M),6.8K

g(3.6M),不含包装

订购模型

Model	Length		Finish
OS2CPS01 OS2CPS04 OS2CPS08 OS2CPS12	01 0.3M Suspended Channel04 1.2M Suspended Channel08 2.4M Suspended Channel12 3.6M Suspended Channel	Direct and/or Indirect Compatible Connected Power Unit Required See page 44 (sold separately)	BK Black WT White

示例: OS2CPS01-BK

TRIG

Model	Description	Pic
	Trig with Feed	1 -
OS2CPS-FTRIG-BK	Includes 96in feed wire, and 2 channel	
OS2CPS-FTRIG-WT	connectors. Suspension Hardware sold	
	separately. Aircraft cable only.	

WAC LIGHTING

Suspended Channel

Responsible	e Liahtina®
-------------	-------------

项目名称: 灯位号:

OS2CPS-TRIG-BK OS2CPS-TRIG-WT	Trig Includes 2 channel connectors. Suspension Hardware sold separately. Stem and Aircraft cable compatible.	
OS2CPS-NADP-BK OS2CPS-NADP-WT	Adapter Additional Trig connectors	

吊装连接器配件

Model	Description	Pic
OS2CP-FE-BK OS2CP-FE-WT	Feed End Includes 96in feed wire and 10 wire guides	
OS2CP-I-FI-BK OS2CP-I-FI-WT	I Connector with Feed Includes 96in of feed wire and 10 wire guides	
OS2CP-I-BK OS2CP-I-WT	I Connector Joins two sections of channel with electrical continuity	
OS2C-ID-BK OS2C-ID-WT	Dead I Connector Joins two sections of channel without electrical continuity	

WAC LIGHTING

Suspended Channel

i iesponsible Ligitining	le Lighting [®]	Responsib
--------------------------	--------------------------	-----------

项目名称:		灯位号:
OS2CPS-L-BK OS2CPS-L-WT	L Connector Joins two channel sections 90°. Feed separately	
OS2CPS-T-BK OS2CPS-T-WT	T Connector Joins three channel sections. Feed separately	
OS2CPS-X-BK OS2CPS-X-WT	X Connector Joins four channel sections. Feed separately	
OS2CPST-IC-BKBK OS2CPST-IC-BKWT OS2CPST-IC-WTWT OS2CPST-IC-WTBK	Surface/Suspended to Recessed Corner Joins suspended or surface mounted channel to recessed trim channel	
OS2CPSL-IC-BKBK OS2CPSL-IC-WTBK	Surface/Suspended to Recessed Corner Joins suspended or surface mounted channel to recessed trimless channel	
OS2CPS-EC-BK OS2CPS-EC-WT	End Cap Additional end cap	

吊装配件 Model

Description

Pic

WAC LIGHTING

Suspended Channel

Responsible Lighting®

项目名称:		灯位号:
OS2CP-CP-BK OS2CP-CP-WT	Cable Canopy Covers a standard 4in junction box. Use with cable feed connectors	
OS2C-C96-BK OS2C-C96-NI	Cable Suspension Support recessed channel from plenum ceiling. Includes 96in aircraft cable; may be field cut	
OS2C-SC96-BK OS2C-SC96-NI	Sloped Ceiling Cable Suspension Suspend channel from a sloped ceiling. Includes 96in aircraft cable; may be field cut	
OS2C-FS96-BK OS2C-FS96-WT	Stem Feed Suspension Suspend channel from ceiling with feed. Includes two 48in stem; may be field cut	
OS2C-S96-BK OS2C-S96-WT	Stem Suspension Support recessed channel from plenum ceiling. Includes two 48in stem; may be field cut	
OS2C-SS96-BK OS2C-SS96-WT	Sloped Ceiling Stem Suspension Suspend channel from a sloped ceiling. Includes two 48in stem; may be field cut	
OS2C-LOOP-BK	Suspension Loop Mechanical loop Supports up to 15 lb	

WAC LIGHTING

Suspended Channel Responsible Lighting®

	项目名称:		灯位号:	
•	OS2SN-1-BK	VACANCY/PHOTO SENSOR		
	OS2C-COV08-BK OS2C-COV08-WT	Channel Cover 2.4M 2.4M length may be field cut, Suitable for top or bottom channel coverage.		